(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization

International Bureau





(43) International Publication Date 3 November 2005 (03.11.2005)

PCT

(10) International Publication Number WO 2005/102028 A1

(51) International Patent Classification⁷: A01G 9/08

(21) International Application Number:

PCT/US2004/009308

(22) International Filing Date: 26 March 2004 (26.03.2004)

(25) Filing Language:

Englis

(26) Publication Language:


English

- (71) Applicant (for all designated States except US): TAGAWA GREENHOUSES, INC. [US/US]; 17999 Weld County Road 4, Brighton, CO 80601 (US).
- (72) Inventors; and
- (75) Inventors/Applicants (for US only): TAGAWA, George,
 H. [US/US]; 1141 Bailey Drive, Brighton, CO 80603 (US).
 TAGAWA, Kenneth, K. [US/US]; 17999 Weld County
 Road 4, Brighton, CO 80601 (US). TAGAWA, Randall,

- E. [US/US]; 513 Columbine Street, Broomfield, CO 80020 (US). **BLACKMORE**, **Fred**, **Naylor**. [US/US]; 4750 Willow Road, Saline, MI 48176 (US).
- (74) Agent: WIEDMANN, Alfred, K.; Santangelo Law Offices, P.C., 125 South Howes, Third Floor, Fort Collins, CO 80521 (US).
- (81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH,

[Continued on next page]

(54) Title: PLANT PUNCH METHODS AND APPARATUS



(57) Abstract: Embodiments focus on imparting a horizontally shifting motion to a plant punch element (1) during a part of a plant punch cycle (18) so as to reduce contact of a plant punching surface (38) with the plant during the plant punch. Plant punch elements that are particularly suited for such "shifting" capability may include a gap (41) facilitating lateral movement of the plant punch element to a position around at least part of the plant to be punched. Aspects of the inventive technology also address a sheltering plant punch apparatus that can also reduce injury and stress experienced by the plant while it is punched. Combinations of aspects disclosed herein provide a high degree of protection to the plant during a plant punch, thereby reducing stress experienced by the plant during the punch.

WO 2005/102028 A1

GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

with international search report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.